

Rosslare's EX-07 is a part of a powerful line of high quality piezoelectric switches. Designed in mind of industrial and high-risk environmental requirements, the EX-07 will adapt well in mines, oil rigs and refineries, military installations, and more. The advanced digital switch offers features such as buzzer mode, lighting mode, and full dual-relay output. It can be used in many hi-demanding applications, from heavy machinery and mechanical operation panels, to access control systems or direct door control.

GENERAL DESCRIPTION

Rosslare's EX-07 is a heavy duty, non-sparking, non-magnetic, corrosion resistant, illuminated, anti-vandal, timed digital switch, designed for both indoor and outdoor use.

It features solid state Piezoelectric Switch Technology generating two isolated Form C output relays with no physical movement or moving parts.

Among its many features are: Jumper selectable illumination status with light dimming option, buzzer mode, full dual-relay output, timed operation and relay toggle option.

MAIN FEATURES

- Advanced soft touch piezoelectric switch
- New weatherproof design water and dust proof, grease, oil and other chemical solvent repellent
- Vandal resistant
- Stainless steel mounting plate and tactile button with no moving parts
- Mounting Method Single Gang: Mounts directly to a US gang switchbox

 Backed by Rosslare's International Guarantee and service with ISO9001 (Certified TÜV Rhineland) level business and manufacturing operations

PROFFESIONAL GRADE FEATURES

- Non-sparking, non-magnetic, corrosion resistant
- Light square status indicator and accidental activation hindrance
- Adjustable Output and Led indication time of 1 to 60 seconds
- Output and indication toggle option
- Jumper selectable illumination status: red, green, or no illumination
- Built-in buzzer with alarm input and sound upon button press options
- Two separate full form-C relay outputs for separate application wiring: N.O. and N.C.
- Input for external lighting alerts for evacuation and other applications



SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

12-24 VAC / VDC One dry contact relay with two separate full Form C outputs Standby 15 mA @ 24 VDC Maximum less than 150 mA @ 24 VDC Over 1 Billion Cycles 100,000 @ 2 A 24 VDC 500,000 @ 1 A 24 VDC
Standby 15 mA @ 24 VDC Maximum less than 150 mA @ 24 VDC Over 1 Billion Cycles 100,000 @ 2 A 24 VDC
Maximum less than 150 mA @ 24 VDC Over 1 Billion Cycles 100,000 @ 2 A 24 VDC
100,000 @ 2 A 24 VDC
Suitable for indoor and outdoor use (meets IP-65)
-35°C to 66°C (-31°F to 151°F)
0 to 85% (non-condensing)
Stainless steel faceplate and button
11.4 x 7 x 3.2 cm (4.5 x 2.75 x 1.25 in.)
277 g (9.8 oz)
Selectable Toggle or timed Pulse
Selectable LED control or alarm
Selectable 1-60 seconds
Off, Red, and Green
Off, On (selectable between alarm input mode and buzzer beep upon button press mode)
For evacuation and other applications
No Text
"PUSH TO EXIT"
External mounting metal box
The EX-07 is compatible with all switch operated electrical device. The unit also works with all of Rosslare's Access control units as well as all standard access control systems.
5-year Limited Product Warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe; and the quality and affordability of a vertically integrated and self-owned manufacturing facility. Our expansive product range features much more than access control solutions and guard patrol management systems; we also offer applications software – such as License Plate Recognition, Time & Attendance, and DVR/alarm integration.

www.rosslaresecurity.com









5505-0114101-02 Copyright © Rosslare