

MD-25TB

Secure Relay I/O Module



THE MD-25TB IS A SECURE RELAY I/O MODULE THAT CONVERTS ROSSLARE'S CONVERTIBLE SERIES (AYC) READERS INTO SECURE STANDALONE CONTROLLERS. WITH THE SECURE MODULE INSTALLED INSIDE THE SECURE PREMISES, CRITICAL WIRING FOR INPUTS, OUTPUTS, REX, AND LOCK ARE INSIDE THE SECURE PREMISES AWAY FROM EXTERNAL MANIPULATION. THE SECURE MODULE SUPPLIES POWER TO THE CONTROLLER AND UTILIZES A PROPRIETARY TWO-WAY PROTOCOL TO COMMUNICATE WITH THE CONTROLLER. THE MD-25TB MAY BE WALL MOUNTED OR INSTALLED IN THE ME-0515M MULTIPURPOSE POWER MANAGEMENT ENCLOSURE.

GENERAL DESCRIPTION

The MD-25TB isolates the lock from the Controller Unit, securing lock functionality when the Controller Unit is tampered with on the outside of the secure premises.

The proprietary two-way protocol allows the Controller Unit to activate the Lock/Auxiliary relays and activate the built-in speaker (for bell, chime, and siren) in the Secure Module, while the Secure module can also communicate REX input status to the Controller Unit.

If the data line between the Controller Unit and the secure module is cut, the system detects the data line has been tampered with and generates a one-minute siren and closes the lock output.

The MD-25TB is designed to be used together with Rosslare's ME-0515M Multipurpose Power Management Enclosure, providing optimum performance and convenience together with universal AC input and a UPS using a Sealed Lead Acid backup battery inside a spacious metal enclosure.

MAIN FEATURES

- Secure Relay I/O Module for use with Rosslare's convertible series readers (AYC)
- Activates the Lock / Auxiliary Relays and the Built-In Speaker for Bell, Chime and Siren tones
- Returns REX status back to the controller unit

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Input	12VDC 2A
■ Output	12VDC 1 A max combined ACU output and lock power supply
■ Lock Output	5 A Form C, SPDT Relay Max Switched Current: 5 A Max Switched Voltage: 150 VDC or 300 VAC UL Rating: 5 A at 30 VDC or 5 A at 125 VAC
■ Auxiliary Output	5 A Form C, SPDT Relay Max Switched Current: 5 A Max Switched Voltage: 150 VDC or 300 VAC UL Rating: 5 A at 30 VDC or 5 A at 125 VAC
■ Speaker Output	0.25 W, 8 Ω (minimum)
■ LED Indicators	Power Status <ul style="list-style-type: none">• Red shows power on• Off shows power off

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Indoor
■ Operating Temperature Range	-10°C - 50°C (14°F - 122°F)
■ Operating Humidity Range	0 to 85% (non-condensing)

MECHANICAL SPECIFICATIONS

■ Enclosure Dimensions	102 x 100 x 35 mm
■ Weight	0.155 kg (0.34 lb)

COMPATABLE DEVICES

The ME-0515M is a compatible device for the MD-25TB.

PRODUCT WARRANTY

2-year limited product warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe.

www.rosslaresecurity.com

5505-0364101-03



• EN ISO 9001



ROSSLARE
Secure Access Solutions